



PRODUCT DATA SHEET

Hyperspec[®] Co-Aligned VNIR-SWIR Sensor



- Wavelength range: 400-2500nm
- Dual VNIR/SWIR Sensors with Co-Aligned Pixels
- 270 & 267 Spectral Pixels (VNIR/SWIR)
- 640 Spatial Pixels

- Small size, low weight
- Suitable for airborne & ground use
- Internal data storage
- All-reflective, concentric optical design

Dual-Sensor VNIR-SWIR Package

Spectral Range	VNIR (400-1000nm)	SWIR (900-2500nm)
Spectrograph Design	High throughput aberration-corrected concentric imager	
Spectral pixels	270	267
Detector Pixel Pitch (microns)	7.4	15
Dispersion per pixel (nm/pixel)	2.2	6
FWHM Slit Image (nm)	6	8
Spatial pixels	640	
f/#	2.5	
Slit width (microns)	20	
Camera Technology	CMOS	Stirling-cooled MCT
Max Frame Rate (Hz)	350	200
Bit Depth	12	16
Size	approx. 10.7" x 8.2" x 6.5" (272mm x 208mm x 165mm)	
Weight (lb / kg)	6.25 / 2.83	

APPLICATIONS



GEOLOGY & MINING



INFRASTRUCTURE INSPECTION



ENVIRONMENTAL

April 2018

© 2018 Headwall Photonics, Inc. Information in this document is subject to change without notice. Headwall Photonics, Inc. reserves the right to change or improve its products and specifications and to make changes in content without obligation to notify any person or organization of such changes or improvements. The Hyperspec® name (and all its derivations) is a registered Trademark of Headwall Photonics, Inc. *US and/or EU Export Restrictions may apply to this Dual Use Product.

contact information

Headwall Photonics, Inc.
 580 Main Street • Bolton, Massachusetts 01740
 978-353-4100
information@headwallphotonics.com